

AIR BRAKE, TYPE A- SAE J1402 & D.O.T. FMVSS 106

Designed for truck and trailer manufacturers, aftermarket packagers and wholesalers, this Air Brake hose conveys air in truck and trailer brake systems. It is certified to meet D.O.T. FMVSS 106 and SAE J1402A requirements and features an EPDM tube and cover with 4-spiral reinforcement making this hose virtually kink proof.



RESISTANCE



BRANDING

Air Brake 3/8" A SAE J1402 Made In USA D.O.T. KX 3/8 (9.5mm) A
 Air Brake 1/2" SP A SAE J1402 Made In USA D.O.T. KX 1/2" SP (12.7mm) A

Cover Color:	Black
Oil Resistance:	Medium
Construction:	
Tube:	EPDM, RMA Class C
Cover:	EPDM, RMA Class C
Reinforcement:	Spiral polyester yarn
Temperature Range:	-40°F to +200°F -40°C to +93°C
Packaging:	Reels, 500 ft. length

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
00482106499	3/8	9.53	0.75	19.05	4	Min. Burst 900	6.20	2.25	57.15	0.17	0.25
00482106498†	3/8	9.53	0.75	19.05	4	Min. Burst 900	6.20	2.25	57.15	0.17	0.25
00482106451**	3/8	9.53	0.75	19.05	4	Min. Burst 900	6.20	2.25	57.15	0.17	0.25
00482108500	1/2	12.70	0.88	22.23	4	Min. Burst 900	6.20	3.00	76.20	0.20	0.30
00482108498†	1/2	12.70	0.88	22.23	4	Min. Burst 900	6.20	3.00	76.20	0.20	0.30
00482108451**	1/2	12.70	0.88	22.23	4	Min. Burst 900	6.20	3.00	76.20	0.20	0.30

† = Maximum 2 pc. 250 ft. reel
 ** = 50 ft. length - 1 per carton