

BLACK RACER™ OS & D

The Black Racer™ Oil Suction and Discharge hose is designed for barge or dock service handling, gasoline, oil and other petroleum products, and meets the U.S. Coast Guard requirements. It features smooth bore construction with a polyester tire cord and wire helix reinforcement with a 200 psi working pressure and full vacuum rating. Available in 100 ft. lengths, this hose reduces the number of connection problems.



RESISTANCE 
BRANDING

Thermoid HBD Industries Inc.
 Black Racer Oil S&D
 Made In USA

Cover Color:	Black
Oil Resistance:	High
Construction:	
Tube:	NBR, RMA Class A
Cover:	CR
Reinforcement:	Polyester tire cord, with a wire helix(es)
Temperature Range:	-20°F to +200°F -29°C to +93°C
Packaging:	100 ft. maximum Hand built – \$250.00 minimum order per size
Couplings:	Constrictor swage couplings

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
34854034002▲	4	101.60	5.00	127.00	4	200	1.38	22.00	558.80	4.20	6.25
34854036002▲	6	152.40	7.13	180.98	4	200	1.38	35.00	889.00	7.60	11.31
34854038002▲	8	203.20	9.19	233.36	4	200	1.38	46.00	1168.40	10.60	15.78

▲ = Make To Order (MTO)

Fixed Flanges

Product Number	Size
34941040001▲	4
34941060001▲	6
34941080001▲	8

▲ = Make To Order (MTO)

Floating Flanges

Product Number	Size
34942040001	4
34942060001	6
34942080001	8

▲ = Make To Order (MTO)

DOCK LOADING

ALERT: Large size, industrial hoses have caution and/or safety usage printed information attached by tag to the product or this information is printed onto the hose.