

## TRANSPORTER® CHEMICAL V

The Transporter Chemical V hose is capable of handling aromatic and aliphatic hydrocarbons and halo generated hydrocarbons, as well as animal oil, vegetable oil, and a wide range of chemicals. Its NBR/PVC cover is both oil and abrasion resistant, and its reinforcement of a spiral steel helix between synthetic textile plies enables this hose to be rated at full vacuum.



**RESISTANCE**     
**BRANDING** HBD Industries Transporter  
 Chemical V Made In USA

**Cover Color:** Orange  
**Oil Resistance:** Medium  
**Construction:**  
**Tube:** FKM, 1–1/2" and 2" I.D. – 1/8" thick  
 3" I.D. and larger – 3/16" thick  
 Exceeds RMA Class A  
**Cover:** NBR/PVC  
**Reinforcement:** Spiral steel wire helix(es) between  
 synthetic textile plies  
**Temperature Range:** -20°F to +250°F  
 -29°C to +121°C

Consult the Chemical Resistance Guide for specific  
 chemical/temperature recommendations.

**Packaging:** 100 ft. maximum  
**Minimum Run:** Available in straight ends, uncapped only

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17701115002▲	1-1/2	38.10	2.06	52.39	2	150	1.03	4.00	101.60	1.20	1.79
17701120002▲	2	50.80	2.56	65.09	2	150	1.03	6.00	152.40	1.50	2.23
17701130002▲	3	76.20	3.69	93.66	2	150	1.03	9.00	228.60	2.40	3.57
17701140002▲	4	101.60	4.69	119.06	2	100	0.69	12.00	304.80	3.40	5.06

▲ = Make To Order (MTO)

Consult coupling manufacturers for specific coupling recommendations/attachment procedures.