

AUTOMOTIVE FI-PLUS FUEL INJECTION SAE 30R9

Designed for the extremely high temperatures generated by fuel injected engines, this hose handles E-85, diesel, biodiesel and extended gasolines while resisting sour gas oxidation. The burst pressure rating of this hose is 900 PSI.



Representative image photo see BRANDING below for product stamp.

BRANDING: Size (mm) I.D. SAEJ30R9 Fuel Injection Hose KXT (lot) meets low permeation requirements per CARB executive order Q-09-026 COVER COLOR: Black		CONSTRUCTION TUBE: Fluoroelastomer COVER: Synthetic Oil Resistant REINFORCEMENT: 2-Spiral Aramid Fiber		TEMPERATURE RANGE: -29°F to +275°F, 33°C +135°C (+302°F 150°C Intermittent) SPECIFICATIONS: SAE30R9	
Thermoid Product Code	Automotive Product Number	Inside Diameter (in)	Length (ft)	Standard Pack Quantity	Approx. Ship Count Wt. (lbs)
0070000502	FI-502	¼	10	1 per Carton	1.0
00700005025	FI-5025	¼	25	1 per Spool	2.5
0070000503	FI-503	⅝	10	1 per Carton	1.4
00700005035	FI-5035	⅝	25	1 per Spool	3.5
0070000504	FI-504	⅜	10	1 per Carton	1.7
00700005045	FI-5045	⅜	25	1 per Spool	4.0