


BLACK MONOFILAMENT BELTING



Description:	[size"]x3P MONO200 BLK NAT BBxBB (S40) (3) PACK-EZ
Product Number	<ul style="list-style-type: none"> • 24303365722 • 24303365602 Belt Length 540' and Above • 24303365603 Belt Length 539' and Below • 24303365482 Belt Length 540' and Above • 24303365483 Belt Length 539' and Below
Product Construction	BARE X BARE (Black Natural Rubber on Mono/Poly Fabric)
Color	Black
Compound Formulation	Natural
Fabric	Monofilament/Polyester
Nominal Overall Gauge	0.165 ± 0.020 in (4.2 ± 0.5 mm)
Nominal Weight	0.96 ±10% lbs./ft ² (4.68 ±10% kg/m ²)
Rated Working Tension	200 lbs./inch (35.0 N/mm)
Top Cover Surface	Bare
Bottom Cover Surface	Bare
Minimum Pulley Diameter	4 in (101 mm)
Temperature Range	-20° to +180°F (-28° to +82°C)
Special Standards	ASTM D378 Flame Test – 60 seconds max
Cover Coefficient of Friction	0.18 max Steel (0.20 max Cardboard)
Bottom Coefficient of Friction, Steel	0.18 max Steel (0.20 max Cardboard)
Available Width(s)	47.5", 59.5", 72"
Typical Applications	<ul style="list-style-type: none"> • Package Handling • Warehouse and distribution center package and tote handling
Benefits	<ul style="list-style-type: none"> • Special fabric for low coefficient friction • Great tracking properties for slider bed usages • Fire Resistant compounds to ASTM D378 Flame Test – 60 seconds max

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.