

BLACK MONOFILAMENT BELTING





Description:	72"x2P MONO90 BLK NAT LIXBB (S40) (3) PACK-EZ
Product Number	24302465722
Product Construction/Plies	Light Impression x Bare (Black Natural Rubber on Mono/Poly Fabric)
Color	Black
Compound Formulation	Natural Rubber
Fabric	Monofilament/Polyester
Nominal Overall Gauge	0.125 ± 0.020 in (3.17 ± 0.50 mm)
Nominal Weight	0.79 ±10% lbs./ft2 (3.67 ±10% kg/m2)
Rated Working Tension	90 lbs./in (16 N/mm)
Top Cover Surface	Light Impression
Bottom Cover Surface	Bare
Minimum Pulley Diameter	2 in (50 mm)
Temperature Range	-20° to +180°F (-28° to +82°C)
Specials Standards	ASTMD378 Flame Test 60 sec. max
Cover Coefficient of Friction	1 Nominal
Bottom Coefficient of Friction, Steel	0.18 max Steel (0.20 max Cardboard)
Available Width(s)	48", 60" and 72"
Typical Applications	 Package Handling Warehouse and distribution center package and tote handling where an incline, decline, or speed up belt is needed Power Turn Belts
Benefits	 Special fabric for low coefficient friction Great tracking properties for slider bed usages Fire resistant compounds to ASTM D378 flame test - 60 seconds max Light Impression top cover helps grip the product when needed

Phone: 800-543-8070 Email: info@thermoid.com

www.thermoid.com

Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.