

CARIPACK[™] – **BLACK RUBBER BELTING**





Description:	72"x3P PCB105 BLK SYN FSxFS (S10) CARIPACK
Product Number	 24553125722 Belt Length 540' and Above 24553125723 Belt Length 539' and Below
Product Construction	Friction X Friction (Black Synthetic on Polyester/Cotton Fabric)
Color	Black
Compound Formulation	Synthetic
Fabric	Polyester/Cotton
Nominal Overall Gauge	0.135 ± 0.020 in (3.4 ± 0.5 mm)
Nominal Weight	0.69 ±10% lbs./ft2 (3.37 ±10% kg/m2)
Rated Working Tension	105 lbs./inch (18 N/mm)
Top Cover Surface	Friction
Bottom Cover Surface	Friction
Minimum Pulley Diameter	4 in (101 mm)
Temperature Range	-30° to +180°F (-34° to +82°C)
Cover Coefficient of Friction	NA Steel (NA Cardboard)
Bottom Coefficient of Friction	0.30 to -0.35 max Steel (0.35 t0 -0.40 max Cardboard)
Available Width(s)	72"
Typical Applications	 Package Handling General purpose unit handling conveyor belt Used as general-purpose belts for slider bed and live roller conveyers where oil is not present Light industrial and automation belts for oil-free service
Benefits	 Good all-around properties for horizontal systems Polyester/cotton blend gives good fastener holding ability

Phone: 800-543-8070 Email: <u>info@thermoid.com</u> <u>www.thermoid.com</u>

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.