

DIAMOND INCLINE – BLACK RUBBER BELTING



Description:	72" x 2P APT150 BLK SYN DIAxTD (S50)
Product Number	24892079722
Product Construction	Diamonds X Treated Duck (Synthetic Rubber on Treated Polyester Fabric)
Color	Black
Compound Formulation	Synthetic Rubber
Fabric	Treated Polyester
Nominal Overall Gauge	0.286 ± 0.032 in (7.25 ± 0.8 mm)
Nominal Weight	1.15 ± 10% lbs./ft ² (5.61 ± 10% kg/m ²)
Rated Working Tension	150 lbs./inch (26 N/mm)
Top Cover Surface	Diamond Incline
Bottom Cover Surface	RFL treated fabric
Minimum Pulley Diameter	4.0 in (101.0 mm)
Temperature Range	-30° to +180°F (-34° to +82°C)
Cover Coefficient of Friction, Steel	1.0 nominal (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.30 max Steel (0.32 max Cardboard)
Available Width(s)	72"
Typical Applications	<ul style="list-style-type: none"> • Incline/Impression • Ideal for package handling on steep incline/decline angles up to 45°
Benefits	<ul style="list-style-type: none"> • Polyester fabric has low stretch and offers excellent fastener retention • Treated duck bottom has low coefficient of friction for slider bed applications • Softer rubber cover provides excellent grip without the need for siping

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.