


DIAMOND INCLINE – TAN RUBBER BELTING



Description:	72"x2P APT150 TAN SYN DIAxTD (S50)
Product Number	24722079722 Belt Length 540' and Above 24722079723 Belt Length 539' and Below
Product Construction	Diamond X Treated Duck (Natural/Synthetic on Treated Polyester Fabric)
Color	Tan
Compound Formulation	Natural/Synthetic
Fabric	Treated Polyester
Nominal Overall Gauge	0.290 ± 0.031 in (7.4 ± 0.8 mm)
Nominal Weight	1.27 ±10% lbs./ft ² (6.20 ±10% kg/m ²)
Rated Working Tension	150 lbs./inch (26 N/mm)
Top Cover Surface	Diamond Incline
Bottom Cover Surface	Treated Duck
Minimum Pulley Diameter	4.0 in (101.0 mm)
Temperature Range	-30° to +180°F (-34° to +82°C)
Cover Coefficient of Friction	1.0 nominal Steel (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.30 max Steel (0.32 max Cardboard)
Available Width(s)	72"
Typical Applications	<ul style="list-style-type: none"> • Incline/Impression • Ideal for package handling on steep incline/decline angles up to 45°
Benefits	<ul style="list-style-type: none"> • Polyester fabric has low stretch and offers excellent fastener retention • Cover compound is non-marking natural rubber • Softer rubber cover provides excellent grip without the need for siping

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.