

### GRIPTOP™ – BLACK RUBBER BELTING



<b>Description:</b>	72"x2P PNT150 BLK SYN RTxTD (S20)
<b>Product Number</b>	24920125722
<b>Product Construction</b>	Rough Top X Treated Duck (Black Synthetic on Treated Polyester/Nylon Fabric)
<b>Color</b>	Black
<b>Compound Formulation</b>	Synthetic
<b>Fabric</b>	Treated Polyester/Nylon
<b>Nominal Overall Gauge</b>	0.240 ± 0.031 in (6.1 ± 0.8 mm)
<b>Nominal Weight</b>	1.00 ±10% lbs./ft <sup>2</sup> (4.88 ±10% kg/m <sup>2</sup> )
<b>Rated Working Tension</b>	150 lbs./inch (26 N/mm)
<b>Top Cover Surface</b>	Rough Top
<b>Bottom Cover Surface</b>	Treated Duck
<b>Minimum Pulley Diameter</b>	2.5 in (64 mm)
<b>Temperature Range</b>	-20° to +180°F (-29° to +82°C)
<b>Cover Coefficient of Friction</b>	1.0 nominal Steel (1.0 nominal Cardboard)
<b>Bottom Coefficient of Friction</b>	0.30 max Steel (0.32 max Cardboard)
<b>Available Width(s)</b>	72"
<b>Typical Applications</b>	<ul style="list-style-type: none"> <li>• General incline/decline conveying</li> <li>• Package handling belts for inclines</li> <li>• Light industrial and automation belts when oil is present</li> </ul>
<b>Benefits</b>	<ul style="list-style-type: none"> <li>• Rough top textured surface with raised rubber peaks grips each package and carries up inclines</li> <li>• Offers excellent fastener ability</li> </ul>

Phone: 800-543-8070

Email: [info@thermoid.com](mailto:info@thermoid.com)

[www.thermoid.com](http://www.thermoid.com)

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.