


GRIPTOP™ – BLACK RUBBER BELTING



representative image

Description:	72"x3P PCB105 BLK SYN RTxFS (S0)
Product Number	<ul style="list-style-type: none"> • 24920139722 Belt Length 540' and Above • 24920139723 Belt Length 539' and Below
Product Construction	Rough Top X Friction (Black Synthetic on Polyester & Cotton/Polyester Fabric)
Color	Black
Compound Formulation	Synthetic
Fabric	Polyester & Cotton/Polyester
Nominal Overall Gauge	0.300 ± 0.031 in (7.6 ± 0.8 mm)
Nominal Weight	1.12 ±10% lbs./ft ² (5.47 ±10% kg/m ²)
Rated Working Tension	105 lbs./inch (18 N/mm)
Top Cover Surface	Rough Top
Bottom Cover Surface	Friction
Minimum Pulley Diameter	4 in (101 mm)
Temperature Range	-30° to +180°F (-34° to +82°C)
Cover Coefficient of Friction	1.0 nominal Steel (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.30 to 0.35 max Steel (0.35 to 0.40 max Cardboard)
Available Width(s)	72"
Typical Applications	<ul style="list-style-type: none"> • General incline/decline conveying • Package handling belts for inclines • Light industrial and automation belts when oil is present
Benefits	<ul style="list-style-type: none"> • Rough top textured surface with raised rubber peaks grips each package and carries up inclines • Offers excellent fastener ability

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.