


### GRIPTOP™ – BLUE CARBOXYLATED NITRILE BELTING



*representative image*

<b>Description:</b>	72"x3P APT225 BLU XNBR RTxTD (S30) (4)
<b>Product Number</b>	<ul style="list-style-type: none"> <li>24920127722 Belt Length 540' and Above</li> <li>24920127723 Belt Length 539' and Below</li> </ul>
<b>Product Construction</b>	Rough Top X Treated Duck (Blue Carboxylated Nitrile on Treated Polyester Fabric)
<b>Color</b>	Blue Cover/Black Skims
<b>Compound Formulation</b>	Carboxylated Cover/Nitrile Skims
<b>Fabric</b>	Treated Polyester
<b>Nominal Overall Gauge</b>	0.320 ± 0.032 in (8.12 ± 0.5 mm)
<b>Nominal Weight</b>	1.390 ±10% lbs./ft <sup>2</sup> (6.78 ±10% kg/m <sup>2</sup> )
<b>Rated Working Tension</b>	225 lbs./inch (39 N/mm)
<b>Top Cover Surface</b>	Rough Top
<b>Bottom Cover Surface</b>	Treated Duck
<b>Minimum Pulley Diameter</b>	4 in (100 mm)
<b>Temperature Range</b>	20° to +212°F (-6° to +100°C)
<b>Cover Coefficient of Friction</b>	1.0 nominal Steel (1.0 nominal Cardboard)
<b>Bottom Coefficient of Friction</b>	0.30 max Steel (0.32 max Cardboard)
<b>Available Width(s)</b>	72"
<b>Typical Applications</b>	<ul style="list-style-type: none"> <li>General incline/decline conveying</li> <li>Where abrasion resistance is needed</li> <li>Paper and cardboard production and converting</li> </ul>
<b>Benefits</b>	<ul style="list-style-type: none"> <li>Configuration good for incline service</li> <li>Carboxylated nitrile offers excellent abrasion, chemical and oil resistance</li> <li>Rough top textured surface grips material on incline use</li> </ul>

Phone: 800-543-8070

Email: [info@thermoid.com](mailto:info@thermoid.com)

[www.thermoid.com](http://www.thermoid.com)

/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.