


GRIPTOP™ – BLUE CARBOXYLATED NITRILE BELTING



representative image

Description:	72"x3P APT225 BLU XNBR RTxTD (S30) (4)
Product Number	24920127722
Product Construction	Rough Top X Treated Duck (Blue Carboxylated Nitrile on Treated Polyester Fabric)
Color	Blue Cover/Black Skims
Compound Formulation	Carboxylated Cover/Nitrile Skims
Fabric	Treated Polyester
Nominal Overall Gauge	0.320 ± 0.032 in (8.12 ± 0.5 mm)
Nominal Weight	1.390 ±10% lbs./ft ² (6.78 ±10% kg/m ²)
Rated Working Tension	225 lbs./inch (39 N/mm)
Top Cover Surface	Rough Top
Bottom Cover Surface	Treated Duck
Minimum Pulley Diameter	4 in (100 mm)
Temperature Range	20° to +212°F (-6° to +100°C)
Cover Coefficient of Friction	1.0 nominal Steel (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.30 max Steel (0.32 max Cardboard)
Available Width(s)	72"
Typical Applications	<ul style="list-style-type: none"> • General incline/decline conveying • Where abrasion resistance is needed • Paper and cardboard production and converting
Benefits	<ul style="list-style-type: none"> • Configuration good for incline service • Carboxylated nitrile offers excellent abrasion, chemical and oil resistance • Rough top textured surface grips material on incline use

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.