

## $GRIPTOP^{TM} - RED/BROWN NITRILE BELTING$





Description:	72"x3P PN150 R/B NBR RTxFS (S10)
Product Number	<ul> <li>24213421722 Belt Length 540' and Above</li> <li>24213421723 Belt Length 539' and Below</li> </ul>
Product Construction	Rough Top X Friction (Red/Brown Nitrile on Polyester/Nylon Fabric)
Color	Red/Brown
Compound Formulation	Nitrile
Fabric	Polyester/Nylon
Nominal Overall Gauge	0.275 ± 0.031 in (7.0 ± 0.8 mm)
Nominal Weight	1.14 ±10% lbs./ft² (5.57 ±10% kg/m²)
Rated Working Tension	150 lbs./inch (26 N/mm)
Top Cover Surface	Rough Top
Bottom Cover Surface	Friction
Minimum Pulley Diameter	3 in (76 mm)
Temperature Range	20° to +212°F (-7° to +100°C)
Cover Coefficient of Friction	1.0 nominal Steel (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.30 to 0.35 max Steel (0.35 to 0.40 max Cardboard)
Available Width(s)	72"
Typical Applications	<ul> <li>Incline/Impression</li> <li>Ideal for package handling on steep incline/decline angles up to 35°</li> </ul>
Benefits	<ul> <li>Excellent oil resistance in applications where oil might be present</li> <li>Rough top textured surface grips material on incline/decline</li> </ul>

Phone: 800-543-8070 Email: <a href="mailto:info@thermoid.com">info@thermoid.com</a> <a href="mailto:www.thermoid.com">www.thermoid.com</a>

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.