


GRIPTOP™ – TAN RUBBER BELTING



Description:	72"x2P APT150 TAN SYN RTxTD (S30)
Product Number	24692452722
Product Construction	Rough Top X Treated Duck (Tan Natural/Synthetic on Treated Polyester Fabric)
Color	Tan
Compound Formulation	Natural/Synthetic
Fabric	Treated Polyester
Nominal Overall Gauge	0.249 ± 0.031 in (6.3 ± 0.8 mm)
Nominal Weight	1.00 ±10% lbs./ft ² (4.88 ±10% kg/m ²)
Rated Working Tension	150 lbs./inch (26 N/mm)
Top Cover Surface	Rough Top
Bottom Cover Surface	Treated Duck
Minimum Pulley Diameter	2.5 in (64 mm)
Temperature Range	-20° to +180°F (-29° to +82°C)
Cover Coefficient of Friction	1.0 nominal Steel (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.30 max Steel (0.32 max Cardboard)
Available Width(s)	72"
Typical Applications	<ul style="list-style-type: none"> • General incline/decline conveying • Agriculture incline service • Light industrial & automation belts when oil is present
Benefits	<ul style="list-style-type: none"> • Rough top textured surface with raised rubber peaks grips each package and carries up inclines • Offers excellent fastener ability • Tan surface is non-marking

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.