


HOT 'N COLD – WHITE BUTYL BELTING



Description:	72"x3P APT105 WHT BTYL 1/32xFS (S10) (1,2) HOT/COLD
Product Number	<ul style="list-style-type: none"> 24243721722 Belt Length 540' and Above 24243721723 Belt Length 539' and Below
Product Construction	Smooth X Friction (White Butyl on Treated Polyester Fabric)
Color	White
Compound Formulation	Butyl
Fabric	Treated Polyester
Nominal Overall Gauge	0.112 ± 0.020 in (2.8 ± 0.50 mm)
Nominal Weight	0.75 ±10% lbs./ft ² (3.66 ±10% kg/m ²)
Rated Working Tension	105 lbs./inch (18 N/mm)
Top Cover Surface	Smooth
Bottom Cover Surface	Friction
Minimum Pulley Diameter	2 in (4 below 0 °F); 51 mm (101 below -18°C)
Temperature Range	-65° to +300°F (-54° to +149°C)
Special Standards	USDA/FDA Approved
Cover Coefficient of Friction	1.0 nominal Steel (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.30 to 0.35 Steel (0.35 to 0.40 Cardboard)
Available Width(s)	72"
Typical Applications	<ul style="list-style-type: none"> Hot Food Dairies or bakeries (temperature conditions) Meats, poultry and bakery Fruit and vegetable processing Frozen foods (sub-zero temperatures)
Benefits	<ul style="list-style-type: none"> Butyl compound is designed for temperatures from -65°F to +300°F Polyester fabric is low stretch and moisture resistant

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.