


### HOT STOCK & WATER – BLACK BELTING



<b>Description:</b>	60"x3P PCB105 (30OZ) BLK SYN SHDxFS (S8) HS&W
<b>Product Number</b>	24553011602
<b>Product Construction/Plies</b>	Silver Hard Duck X Friction (Black Synthetic on Polyester/Cotton Fabrics)
<b>Color</b>	Black (Note: Cover is white, but skim rubber is black.)
<b>Compound Formulation</b>	Synthetic
<b>Fabric</b>	Polyester/Cotton
<b>Nominal Overall Gauge</b>	0.145 ± 0.020 in (3.7 ± 0.50 mm)
<b>Nominal Weight</b>	0.59 ±10% lbs./ft <sup>2</sup> (2.88 ±10% kg/m <sup>2</sup> )
<b>Rated Working Tension</b>	105 lbs./in (18 N/mm)
<b>Top Cover Surface</b>	Silver Hard Duck
<b>Bottom Cover Surface</b>	Friction
<b>Minimum Pulley Diameter</b>	2.5 in (64 mm)
<b>Temperature Range</b>	-20° to +250°F (-29° to +121°C)
<b>Cover Coefficient of Friction</b>	NA Steel (NA Cardboard)
<b>Bottom Coefficient of Friction, Steel</b>	0.30 to 0.35 max Steel (0.35 to 0.40 max Cardboard)
<b>Available Width(s)</b>	60"
<b>Typical Applications</b>	<ul style="list-style-type: none"> <li>• Tire manufacturing</li> <li>• Conveys rubber stock in various stages of processing</li> <li>• Horizontal conveying systems where a bare fabric surface is preferred</li> </ul>
<b>Benefits</b>	<ul style="list-style-type: none"> <li>• Silver hard duck cotton to ply prevents hot rubber from sticking to belt surface</li> <li>• Friction surface bottom gives low coefficient of friction on slider beds</li> </ul>

Phone: 800-543-8070

Email: [info@thermoid.com](mailto:info@thermoid.com)

[www.thermoid.com](http://www.thermoid.com)

Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.