

### HOT STOCK & WATER – BIG RED SILICONE BELTING



<b>Description:</b>	60"x3P PCB105 BLK SYN SILxFS (S8) HS&W
<b>Product Number</b>	24553018602
<b>Product Construction</b>	Silicone X Friction (Black Synthetic on Polyester/Cotton Fabric)
<b>Color</b>	Red ( <i>Note: Cover is red, but skim rubber is black</i> )
<b>Compound Formulation</b>	Synthetic
<b>Fabric</b>	Polyester/Cotton
<b>Nominal Overall Gauge</b>	0.152 ± 0.020 in (3.9 ± 0.5 mm)
<b>Nominal Weight</b>	0.65 ±10% lbs./ft <sup>2</sup> (3.17 ±10% kg/m <sup>2</sup> )
<b>Rated Working Tension</b>	105 lbs./inch (18 N/mm)
<b>Top Cover Surface</b>	Red Silicone
<b>Bottom Cover Surface</b>	Friction
<b>Minimum Pulley Diameter</b>	4 in (101 mm)
<b>Temperature Range</b>	-20° to +350°F top cover (-29° to +177°C top cover)
<b>Cover Coefficient of Friction</b>	NA Steel (NA Cardboard)
<b>Bottom Coefficient of Friction, Steel</b>	0.30 max Steel (0.25 max Cardboard)
<b>Available Width(s)</b>	60"
<b>Typical Applications</b>	<ul style="list-style-type: none"> <li>• Tire manufacturing</li> <li>• Conveys rubber stock in various stages of processing</li> </ul>
<b>Benefits</b>	<ul style="list-style-type: none"> <li>• Silicone top cover offers excellent resistance to heat</li> <li>• Good release qualities</li> <li>• Rated at higher temperature than standard HS &amp; W belt (250°)</li> </ul>

Phone: 800-543-8070

Email: [info@thermoid.com](mailto:info@thermoid.com)

[www.thermoid.com](http://www.thermoid.com)

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.