


RIDGETOP™ – WHITE NITRILE BELTING



Description:	72"x3P PNT150 WHT NBR RD/TPxFS (S10) (1,2) SANI-BRIGHT
Product Number	24283829722
Product Construction	Ridgetop X Friction (White Nitrile on Treated Polyester/Nylon Fabric)
Color	White
Compound Formulation	Nitrile
Fabric	Treated Polyester/Nylon
Nominal Overall Gauge	0.290 ± 0.031 in (7.4 ± 0.8 mm)
Nominal Weight	1.25 ±10% lbs./ft ² (6.10 ±10% kg/m ²)
Rated Working Tension	150 lbs./inch (26 N/mm)
Top Cover Surface	Ridgetop
Bottom Cover Surface	Friction
Minimum Pulley Diameter	3 in (76 mm)
Temperature Range	20° to +212°F (-6° to +100°C)
Special Standards	USDA/FDA Approved
Cover Coefficient of Friction	1.0 nominal Steel (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.30 max Steel (0.32 max Cardboard)
Available Width(s)	72'
Typical Applications	<ul style="list-style-type: none"> • Food Handling incline up to 30° • Meats, poultry and bakery • Fruit and vegetable processing • Agriculture incline service
Benefits	<ul style="list-style-type: none"> • Molded cleat 1/8" on 1" centers • Carries meat and food products up 20-30° inclines • Offers good resistance to oil, grease, fats, food acids

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.