

### SANI-WHITE™ – WHITE BELTING



*representative image*

<b>Description:</b>	72"x2P PNT100 WHT NBR 3/64xFS (S10) (1,2) SANI-WHITE
<b>Product Number</b>	24282821722
<b>Product Construction</b>	Smooth X Friction (White Nitrile on Treated Polyester/Nylon Fabric)
<b>Color</b>	White
<b>Compound Formulation</b>	Nitrile
<b>Fabric</b>	Treated Polyester/Nylon
<b>Nominal Overall Gauge</b>	0.109 ± 0.020 in (2.8 ± 0.5 mm)
<b>Nominal Weight</b>	0.76 ±10% lbs./ft <sup>2</sup> (3.71 ±10% kg/m <sup>2</sup> )
<b>Rated Working Tension</b>	100 lbs./inch (18 N/mm)
<b>Top Cover Surface</b>	Smooth
<b>Bottom Cover Surface</b>	Friction
<b>Minimum Pulley Diameter</b>	3 in (76 mm)
<b>Temperature Range</b>	20° to +212°F (-7° to +100°C)
<b>Special Standards</b>	USDA/FDA Approved
<b>Cover Coefficient of Friction</b>	1.0 nominal Steel (1.0 nominal Cardboard)
<b>Bottom Coefficient of Friction</b>	0.30 max Steel (0.32 max Cardboard)
<b>Available Width(s)</b>	72'
<b>Typical Applications</b>	<ul style="list-style-type: none"> <li>• Meats, poultry and bakery</li> <li>• Hot, oily foods</li> <li>• Fruit and vegetable processing</li> </ul>
<b>Benefits</b>	<ul style="list-style-type: none"> <li>• Exceptional resistance to oil, grease, fats, food acids and moisture</li> <li>• Smooth cover resists abrasion and makes for easier cleaning</li> <li>• Low stretch and good fastener retention</li> </ul>

Phone: 800-543-8070

Email: [info@thermoid.com](mailto:info@thermoid.com)

[www.thermoid.com](http://www.thermoid.com)

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.