

SANI-BRIGHT™ – WHITE BELTING



Description:	72"x3P PNT150 WHT NBR 0.04xFS (S10) (1,2) SANI-BRIGHT
Product Number	<ul style="list-style-type: none"> 24913021722 Belt Length 540' and Above 24913021723 Belt Length 539' and Below
Product Construction	Smooth X Friction (White Nitrile on Treated Polyester/Nylon Fabric)
Color	White
Compound Formulation	Nitrile
Fabric	Treated Polyester/Nylon
Nominal Overall Gauge	0.135 ± 0.020 in (3.4 ± 0.5 mm)
Nominal Weight	0.83 ±10% lbs./ft ² (4.05 ±10% kg/m ²)
Rated Working Tension	150 lbs./inch (26 N/mm)
Top Cover Surface	Smooth
Bottom Cover Surface	Friction
Minimum Pulley Diameter	3 in (76 mm)
Temperature Range	20° to +212°F (-7° to +100°C)
Special Standards	USDA/FDA Approved
Cover Coefficient of Friction	NA Steel (NA Cardboard)
Bottom Coefficient of Friction, Steel	0.30 max Steel (0.32 max Cardboard)
Available Width(s)	72'
Typical Applications	<ul style="list-style-type: none"> Meats, poultry and bakery Hot, oily foods Fruit and vegetable processing
Benefits	<ul style="list-style-type: none"> Exceptional resistance to oil, grease, fats, food acids and moisture Smooth cover resists abrasion and makes for easier cleaning Low stretch and good fastener retention

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.