


### SANI-WHITE™ – WHITE BELTING



*representative image*

<b>Description:</b>	72"x3P APT105 WHT NBR 1/32x1/32 (S30) (1,2) SANI-WHITE
<b>Product Number</b>	<ul style="list-style-type: none"> <li>24093755722 Belt Length 540' and Above</li> <li>24093755723 Belt Length 539' and Below</li> </ul>
<b>Product Construction</b>	Smooth X Smooth (White Nitrile on Treated Polyester Fabric)
<b>Color</b>	White
<b>Compound Formulation</b>	Nitrile
<b>Fabric</b>	Treated Polyester
<b>Nominal Overall Gauge</b>	0.187 ± 0.031 in (4.7 ± 0.8 mm)
<b>Nominal Weight</b>	1.26 ±10% lbs./ft <sup>2</sup> (6.15 ±10% kg/m <sup>2</sup> )
<b>Rated Working Tension</b>	105 lbs./inch (18 N/mm)
<b>Top Cover Surface</b>	Smooth
<b>Bottom Cover Surface</b>	Smooth
<b>Minimum Pulley Diameter</b>	4 in (102 mm)
<b>Temperature Range</b>	20° to +212°F (-7° to +100°C)
<b>Special Standards:</b>	USDA/FDA Approved
<b>Cover Coefficient of Friction</b>	1.0 nominal Steel (1.0 nominal Cardboard)
<b>Bottom Coefficient of Friction</b>	0.45 to 0.55 Steel (0.40 to 0.50 Cardboard)
<b>Available Width(s)</b>	72"
<b>Typical Applications</b>	<ul style="list-style-type: none"> <li>Meats, poultry and bakery</li> <li>Hot, oily foods</li> <li>Fruit and vegetable processing</li> </ul>
<b>Benefits</b>	<ul style="list-style-type: none"> <li>Matte finish to help reduce eye strain on inspection lines</li> <li>Exceptional resistance to oil, grease, fats, food acids and moisture</li> <li>Smooth cover resists abrasion and makes for easier cleaning</li> <li>Polyester fabric is low stretch and moisture resistant</li> </ul>

Phone: 800-543-8070

Email: [info@thermoid.com](mailto:info@thermoid.com)

[www.thermoid.com](http://www.thermoid.com)

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.