

### SHEETING – RED/BROWN NITRILE BELTING



<b>Description:</b>	72"x3P SCP42 R/B NBR FSxFS (S8)
<b>Product Number</b>	24343111722
<b>Product Construction</b>	Friction X Friction (Red/Brown Nitrile on Special Cotton Blend Fabric)
<b>Color</b>	Red/Brown
<b>Compound Formulation</b>	Nitrile
<b>Fabric</b>	Special Cotton Blend
<b>Nominal Overall Gauge</b>	0.056 ± 0.016 in (1.4 ± 0.4 mm)
<b>Nominal Weight</b>	0.38 ±10% lbs./ft <sup>2</sup> (1.85 ±10% kg/m <sup>2</sup> )
<b>Rated Working Tension</b>	42 lbs./inch (7 N/mm)
<b>Top Cover Surface</b>	Friction
<b>Bottom Cover Surface</b>	Friction
<b>Minimum Pulley Diameter</b>	1.5 in (38 mm)
<b>Temperature Range</b>	20° to +212°F (-7° to +100°C)
<b>Cover Coefficient of Friction</b>	0.30 to 0.35 max Steel (0.35 to 0.40 max Cardboard)
<b>Bottom Coefficient of Friction, Steel</b>	0.30 to 0.35 max Steel (0.35 to 0.40 max Cardboard)
<b>Available Width(s)</b>	72"
<b>Typical Applications</b>	<ul style="list-style-type: none"> <li>• General Industrial</li> <li>• Medium duty sheeting belts for horizontal service to carry cases, cartons and packages</li> <li>• Oily parts conveying</li> </ul>
<b>Benefits</b>	<ul style="list-style-type: none"> <li>• Belt has exceptional resistance to oils, grease, fats, food acids and moisture</li> <li>• Both sides have excellent oil resistance</li> </ul>

Phone: 800-543-8070

Email: [info@thermoid.com](mailto:info@thermoid.com)

[www.thermoid.com](http://www.thermoid.com)

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.