

SHEETING – RED/BROWN NITRILE BELTING



representative image

Description:	72"x7P SCP98 R/B NBR FSxFS (S8)
Product Number	24347111722
Product Construction	Friction X Friction (Red/Brown Nitrile on Special Cotton Blend Fabric)
Color	Red/Brown
Compound Formulation	Nitrile
Fabric	Special Cotton Blend
Nominal Overall Gauge	0.163 ± 0.020 in (4.1 ± 0.5 mm)
Nominal Weight	1.02 ±10% lbs./ft ² (4.98 ±10% kg/m ²)
Rated Working Tension	98 lbs./inch (17 N/mm)
Top Cover Surface	Friction
Bottom Cover Surface	Friction
Minimum Pulley Diameter	3.5 in (89 mm)
Temperature Range	20° to +212°F (-7° to +100°C)
Cover Coefficient of Friction	0.30 to 0.35 max Steel (0.35 to 0.40 max Cardboard)
Bottom Coefficient of Friction	0.30 to 0.35 max Steel (0.35 to 0.40 max Cardboard)
Available Width(s)	72"
Typical Applications	<ul style="list-style-type: none"> • General Industrial • Medium duty sheeting belts for horizontal service to carry cases, cartons and packages • Oily parts conveying
Benefits	<ul style="list-style-type: none"> • Belt has exceptional resistance to oils, grease, fats, food acids and moisture • Both sides have excellent oil resistance

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.