

SLIDE-A-PACK™ BELTING



Description:	72"x3P PCB105 TAN SYN FSxFS (S8) SLIDE-A-PACK
Product Number	24543111722
Product Construction	Friction X Friction (Tan Synthetic on Polyester/Cotton Blend Fabric)
Color	Tan
Compound Formulation	Synthetic
Fabric	Polyester/Cotton Blend
Nominal Overall Gauge	0.131 ± 0.020 in (3.3 ± 0.5 mm)
Nominal Weight	0.69 ±10% lbs./ft ² (3.37 ±10% kg/m ²)
Rated Working Tension	105 lbs./inch (18 N/mm)
Top Cover Surface	Friction
Bottom Cover Surface	Friction
Minimum Pulley Diameter	4 in (101 mm)
Temperature Range	-30° to +180°F (-34° to +82°C)
Cover Coefficient of Friction	0.30 to -0.35 max Steel (0.35 to -0.40 max Cardboard)
Bottom Coefficient of Friction, Steel	0.30 to -0.35 max Steel (0.35 to -0.40 max Cardboard)
Available Width(s)	72"
Typical Applications	<ul style="list-style-type: none"> • Package Handling • General purpose rubber belts for live roller and slider bed operations • Light industrial and automation belts for oil-free service • General conveying and power transmission applications
Benefits	<ul style="list-style-type: none"> • Can be used on slider bed and live roller applications where no oil is present

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.