

SLIPTOP™ – TAN NITRILE BELTING



Description:	72"x4P SCP150 TAN NBR TDxFS (S10) SLIPTOP
Product Number	24424321722
Product Construction	Treated Duck X Friction (Tan Nitrile on Polyester/Cotton and Treated Polyester/Nylon Fabric)
Color	Tan
Compound Formulation	Nitrile Rubber
Fabric	Polyester/Cotton and Treated Polyester/Nylon
Nominal Overall Gauge	0.125 ± 0.020 in (3.2 ± 0.5 mm)
Nominal Weight	0.75 ±10% lbs./ft ² (3.66 ±10% kg/m ²)
Rated Working Tension	150 lbs./inch (26 N/mm)
Top Cover Surface	Treated Duck
Bottom Cover Surface	Friction
Minimum Pulley Diameter	3 in (76 mm)
Temperature Range	20° to +212°F (-7° to +100°C)
Cover Coefficient of Friction	0.30 max Steel (0.32 max Cardboard)
Bottom Coefficient of Friction	0.30 to 0.35 max Steel (0.35 to 0.40 max Cardboard)
Available Width(s)	72"
Typical Applications	<ul style="list-style-type: none"> • Package Handling • Horizontal conveyer systems where easy package release and diverting is required • Light industrial and automation belts
Benefits	<ul style="list-style-type: none"> • Bare treated top has low coefficient of friction for easy package release • Nitrile compound has excellent oil resistance

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.