

TEFLON* - WHITE NITRILE BELTING



Description:	54"x3P AP105 WHT NBR TEFS (S10) (1,2)
Product Number	<ul style="list-style-type: none"> 24023023542 Belt Length 540' and Above 24023023543 Belt Length 539' and Below
Product Construction	Teflon X Friction (White Nitrile on Polyester Fabric)
Color	White
Compound Formulation	Nitrile
Fabric	Polyester
Nominal Overall Gauge	0.094 ± 0.016 in (2.4 ± 0.4 mm)
Nominal Weight	0.55 ±10% lbs./ft ² (2.69 ±10% kg/m ²)
Rated Working Tension	105 lbs./inch (18 N/mm)
Top Cover Surface	Teflon*
Bottom Cover Surface	Friction
Minimum Pulley Diameter	3 in (76 mm)
Temperature Range	20° to +212°F (-7° to +100°C)
Special Standards	USDA/FDA Approved
Cover Coefficient of Friction	NA Steel (NA Cardboard)
Bottom Coefficient of Friction	0.30 to 0.35max Steel (0.35 to 0.40 max Cardboard)
Available Width(s)	54"
Typical Applications	<ul style="list-style-type: none"> Bakery and candy
Benefits	<ul style="list-style-type: none"> Excellent release properties Easy washdown

* Teflon is a registered mark of Chemours Company.

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.