

FUEL LINE, VAPOR EMISSION & CRANKCASE VENTILATION (30R7)

This durable, aftermarket standard hose is used for conveying most automobile, truck and bus fuel and is ideal for equipment, wholesalers, aftermarket packagers and auxiliary tank manufacturers. It provides superior service in temperatures ranging from -29°F to +257°F. Featuring an NBR tube and an NBR/PVC cover reinforced with multiple spiral polyester, the hose remains flexible and resistant to oil, grease, ozone and under-hood temperatures generated by today's automotive engines.



RESISTANCE   
BRANDING Size SAE 30R7-KX Date
 Made In USA

Cover Color: Black
Oil Resistance: Medium-High
Construction:
Tube: NBR, RMA Class A
Cover: NBR/PVC, RMA Class B
Reinforcement: Spiral polyester yarn
Temperature Range: -40°F to +257°F
 -40°C to +125°C
Packaging: See below chart

SAE 30R7: Not recommended for recirculating fuel systems. Product conforms to all SAE 30R7 requirements for non-recirculating systems. SAE 30R9 recommended for recirculating systems.

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight		
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)	
25 ft. Coil												
00667503225	3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10	
00667504225	1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13	
00667505225▲	5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16	
00667506225▲	3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18	
50 ft. Coil												
00667503252▲	3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10	
00667504252▲	1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13	
00667505252▲	5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16	
00667506252▲	3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18	
250 ft. Reel												
00667503298▲	3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10	
00667504298	1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13	
00667505298	5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16	
00667506298	3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18	
500 - 700 ft. Reel												
00667503299	3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10	
00667504299	1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13	
00667505299	5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16	
00667506299	3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18	
00667508299	1/2	12.70	0.781	19.83	2	35	0.24	3.00	76.20	0.16	0.24	

▲ = Make To Order (MTO)