

V-CLEAT – BLACK RUBBER BELTING



Description:	72"x3P PCB105 BLK SYN V/CLxFS (S10)
Product Number	24553029722
Product Construction/Plies	V-Cleat X Friction (Black Natural/Synthetic on Polyester/Cotton Fabric)
Color	Black
Compound Formulation	Natural/Synthetic
Fabric	Polyester/Cotton
Nominal Overall Gauge	0.328 ± 0.032 in (8.3 ± 0.80 mm)
Nominal Weight	1.22 ±10% lbs./ft ² (5.96 ±10% kg/m ²)
Rated Working Tension	105 lbs./inch (18 N/mm)
Top Cover Surface	Black V-Cleat
Bottom Cover Surface	Friction
Minimum Pulley Diameter	4 in (101 mm)
Temperature Range	-30° to +180°F (-34° to +82°C)
Cover Coefficient of Friction	1.0 nominal Steel (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.20 max Steel (0.25 max Cardboard)
Available Width(s)	72"
Typical Applications	<ul style="list-style-type: none"> • Incline/Impression • Ideal for package handling on steep incline/decline angles up to 45°
Benefits	<ul style="list-style-type: none"> • Superior grab on steepest incline applications • Fabric provides good fastener retention • Top cover holds material without damage to articles being conveyed

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.